

Crush resistant exhaust gas hose

Applications

- flexible hose/ ducting for hot gases
- vehicle gas exhaust system, car gas extraction: hose reel, slotted floor channel, underfloor extraction system
- engine test bench, exhaust gas measurement

Properties

- fabric reinforced
- highly flexible + compressible
- protected, flow-optimizing exterior folds
- vibration resistant

- crush resistant
- good resistance to chemicals
- conforms to RoHS guideline

Temperature Range

- exhaust gas temperatures to 200°C *
- * when correctly applied with exhaust gas funnels and sufficient fresh air supply (50% approx.).

Design, Material

patented PROTAPE® tape hose

- special plastic-profile supporting spiral
- fabric-reinforced tape; wall: EPDM/ PP coated fabric
- wall thickness 0,4 mm approx.

Delivery variants

- further diameters and lengths available on request
- black (standard)
- special colours: coloured spiral
- customer-specific branding

I.D. in / mm	O.D. mm	Under- pressure bar	Bending Radius mm	Weight kg/m	Dimensions in Stock m	Order No.
2 / 50-51	68	0,400	57	0,380	10 15	326-0051-0000
2,5 / 63-65	80	0,280	70	0,480	10 15	326-0063-0000
3 / 75-76	93	0,170	73	0,540	5 6 7,5 10 12,5 15	326-0076-0000
4 / 100-102	119	0,050	71	0,710	5 6 7,5 10 12,5 15	326-0102-0000
5 / 125-127	144	0,035	89	0,870	5 6 7,5 10 12,5 15	326-0127-0000
6 / 150-152	169	0,030	106	1,040	5 6 7,5 10 12,5 15	326-0152-0000
8 / 200-203	220	0,010	143	1,370	5 6 7,5 10	326-0203-0000

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional technical data at www.norres.com/en/technology/

Accessories




CLAMP 212



CLAMP 217



CLAMP 213



CONNECT 228



CONNECT 270-271

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. Additional technical data at www.norres.com. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data.